



KEY FEATURES

Pragmalux LED Recessed spotlight Ponto Square is a square recessed spot with 1 or 2- LED modules with a high light output of more than 3000lm and only a cutting size of Ø117mm. This makes this fixture ideal for use as basic light in rooms with a high ceiling or where high light output is essential. The recessed spot can be tilted 30° and is ideally suited for professional use in shops, hotels and showrooms.

In addition, the downlight Ponto has an integrated Philips SLM LED module with a CRI > 90 value, so that colors are displayed excellently. The recessed spot is available in different colors and light beams. This product comes with an external premium Philips Xitanium driver.

IP20 IK03 **CRI ≥ 90** **TILTABLE 30° X 355°** **INSTALLATION 117 mm** **DIMENSIONS 130x130 mm 245x130 mm** **5 YEAR WARRANTY**

OPTIONS
DALI **GST 18i3/5** **CASAMBI** **2700K 4000K**
FASHION MODULE **FOOD MODULE** **15° 24° 60°**
COLORS
W B G

DETAILS



2V version

SPECIFICATIONS

ITEM CODE	DESCRIPTION	W	LM*	LM/W*	KELVIN	LIFETIME L80B10	BEAM ANGLE
9112565	LED Spot Ponto Square 1V 24W 3000K CRI>90 36D 3100lm Grey Ø130x130 F - G Ø117	24	3100	129	3000	50000	36°
9112566	LED Spot Ponto Square 1V 24W 3000K CRI>90 36D 3100lm White Ø130x130 F - G Ø117	24	3100	129	3000	50000	36°
9112567	LED Spot Ponto Square 1V 24W 3000K CRI>90 36D 3100lm Black Ø130x130 F - G Ø117	24	3100	129	3000	50000	36°
9112568	LED Spot Ponto Square 2V 2x24W 3000K CRI>90 36D 2x3100lm Grey Ø245x130 F - G Ø232x112	48	6200	129	3000	50000	36°
9112569	LED Spot Ponto Square 2V 2x24W 3000K CRI>90 36D 2x3100lm White Ø245x130 F - G Ø232x112	48	6200	129	3000	50000	36°
9112570	LED Spot Ponto Square 2V 2x24W 3000K CRI>90 36D 2x3100lm Black Ø245x130 F - G Ø232x112	48	6200	129	3000	50000	36°

* Bruto lumen - LOR up to 85%

DIMENSIONS

